

HT644

Quick Start User Guide



HT644

INTRODUCTION

The HT644 is a commercial-grade VHF marine portable with an IP68 submersible rating. Modes include International, USA and Canadian channels, and weather and private channels.

Your dealer may have customised the radio to meet your exact requirements. They will explain these features in a separate guide.

PACKING LIST

HT644 VHF radio
Li-ion battery pack
Drop in charger
Spring loaded belt clip
High efficiency antenna
Quick start user guide

OPTIONAL ACCESSORIES

Attaching and removing accessories

- To attach an accessory, remove the accessory cover by unscrewing the locking screw anti-clockwise (leave the cover attached or store in a safe place).
- Plug the accessory into the socket, then carefully tighten the locking screw clockwise until finger tight (do not overtighten or use any implement)
- To remove an accessory, unscrew the locking screw of the accessory by hand in an anti-clockwise direction. Ensure you re-fit the accessory socket cover (the radio is not submersible without the socket covered).



BATTERY INFORMATION

Battery charging

- Connect the AC adapter to the charger pod and plug in.
- Turn the radio off.
- Insert the battery pack into the charger pod, either with or without the radio attached. The charger LED status light changes to red and charging begins.
- When charging is complete the charger status LED changes from red to green (a fully discharged battery pack will take approximately 6 hours to recharge).
- For standby / emergency operation charge the battery once a week
- If the battery is used infrequently, e.g. leisure use, ensure it is charged at least once a month.



CAUTION

BATTERY PACK PRECAUTIONS

- Do not recharge the battery pack if it is already fully charged. Doing so may reduce the life of the battery pack.
- After charging is complete, remove the battery from the charger.
- Please ensure that the radio is turned off before placing it in the charger and never switch a radio on whilst in the charger.
- Only use Entel branded battery packs and chargers.
- Do not short the battery terminals or dispose of the battery in a fire.
- Do not charge the radio and/or battery pack if they are wet.

DANGER

DO NOT DISASSEMBLE OR MODIFY THE BATTERY IN ANY WAY!

Your Entel battery pack incorporates a safety circuit to avoid danger, if the safety circuit is damaged or bypassed, or the battery cells are damaged directly, they may generate extreme heat, smoke, rupture and emit flames.

CONTROLS & INDICATORS



1. On/off knob. Rotate to turn the radio on or off, rotate clockwise to increase volume
2. **MEM Button:** Memorises a desired channel for scanning
SCAN Button: Starts/stops scanning the memorized channels
WX Button: Immediately recalls the weather channels
A/B Button: Dealer operation only
3. Channel control
4. Push To Talk (PTT) button. Press to speak and release to listen
5. **16/9 Button:** Short press selects channel 16 and a longer press selects channel 9
6. Toggle high/low transmitter power
7. Short press toggles LCD and keypad backlight on/off. Long press toggles keypad lock on/off
8. Monitor momentarily (squelch defeat)
9. LED Indicator
Red steady - Transmitting
Red flashing slowly - Battery needs recharging
Green steady - Receiving
10. Microphone

PREPARING YOUR RADIO FOR USE

Attaching / removing the antenna



1. To attach, carefully align the antenna with the socket. Screw in the antenna and clockwise (taking care not to cross the thread) until it is seated firmly with the accessory cover's rubber ring between the antenna and the top of the radio. (A)
2. To remove, unscrew the antenna anti-clockwise. (B)

Attaching / removing the battery pack



1. To attach, locate the pegs on the bottom of the battery into the slots on the radio and press the top of the battery against the radio. Secure battery by tightening the screw clockwise by hand. (Do not use any implement or overtighten). (C)
2. To remove, unscrew the locking screw anti-clockwise and pull the battery away from the top of the radio. (D)

SWITCHING ON, RECEPTION AND SWITCHING OFF

1. To switch on, rotate the on/off/volume control (1) on the top of the radio clockwise.
2. The radio will enter standby mode. This is indicated by the LED Amber flashing once every 5 seconds, signalling that the radio is ready for use.
3. Adjust the volume control (1) to select the desired volume level.
4. Using the channel buttons (3) ensure you have the correct channel selected.
5. When receiving a valid signal, the LED will illuminate steady green and audio will be emitted from the radio's speaker or audio accessory (if attached)
6. When finished using the radio, switch off by turning the on/off/volume control (1) until it clicks and the radio will be switched off.

TRANSMITTING

1. Perform steps 1 through to 5 of 'Switching On, Reception and Switching Off.'
2. Before transmitting, monitor the channel and make sure it is clear.
3. When receiving a signal, wait until the signal stops before transmitting. The radio cannot transmit and receive simultaneously.
4. Press the PTT (Push To Talk) button (4) to begin your transmission. To confirm transmission the LED illuminates red.
5. For best transmitted speech quality you must talk directly into the radio's microphone (10) at around 4cm between your mouth and the radio.
6. Please note: if you talk into the top of the radio or with your mouth further away, you will transmit poor quality speech.
7. When the transmission is finished, release the PTT button.

DECLARATION OF CONFORMITY

Hereby, Entel UK Limited
Declares that the radio equipment type
HT644 is in compliance with
Directive 2014/53/EU and Radio Equipment
Regulations 2017.

The full text of the relevant declaration of
conformity is available at the following
internet address:

EU www.entel.co.uk/red

UK www.entel.co.uk/UKCA

The product shall only be put into service
after it has been professionally configured by
a specialist radio communications dealer for
the EU member state or geographical area it
is intended to be operated within.

Intended country of use

	AT	BE	BG	CH	CY	CZ	DE	DK	EE
	ES	FI	FR	EL	HR	HU	IE	IS	IT
	LI	LT	LU	LV	MT	NL	NO	PL	PT
	RO	SE	SI	SK	TR	UK(NI)			

